

Revision nr.2 Dated 8/23/2024 Printed on 8/23/2024 Page n. 1 / 13 Replaced revision:1 (Dated 10/10/2017)

Safety Data Sheet

According to U.S.A. Federal Hazcom 2012

1. Identification

1.1. Product identifier

Code: A-3TO1

Product name **EPOXART RESIN A-3TO1**

1.2. Relevant identified uses of the substance or mixture and uses advised against

LIQUID EPOXY RESINS FOR STONES. Intended use

Identified Uses	Industrial	Professional	Consumer
ADHESIVE SYSTEM/TREATMENT FOR STONE SECTOR	✓	✓	-
1.3. Details of the supplier of the safety data sheet			
Name Full address District and Country	TENAX SPA Via I Maggio 37020	226 Volargne Italy +39 045 6887593	(VR)
e-mail address of the competent person responsible for the Safety Data Sheet	Fax msds@tenax	+39 045 6862456	
Supplier:		831173 - Fax 001 704583316	uite 400, 28273 Charlotte NC, US 6
1.4. Emergency telephone number			
For urgent inquiries refer to	Infotrac US and Cana Int'l: 1-352-3	da: 1-800-535-5053 23-3500	

2. Hazards identification

2.1. Classification of the substance or mixture

The product is classified as hazardous pursuant to the provisions set forth in OSHA Hazard Communication Standard (HCS) (29 CFR 1910.1200). The product thus requires a safety datasheet.

Any additional information concerning the risks for health and/or the environment are given in sections 11 and 12 of this sheet.

info@infotrac.net

Classification and Hazard Statement Germ cell mutagenicity, category 2 Eye irritation, category 2 Skin irritation, category 2 Skin sensitization, category 1

Causes skin irritation. May cause an allergic skin reaction.

Causes serious eye irritation.

Suspected of causing genetic defects.





Signal words: Warning

Hazard statements:

H341 Suspected of causing genetic defects. H319 Causes serious eye irritation.



Revision nr.2 Dated 8/23/2024 Printed on 8/23/2024 Page n. 2 / 13 Replaced revision:1 (Dated 10/10/2017)

.../>> 2. Hazards identification

H315 Causes skin irritation.

H317 May cause an allergic skin reaction.

Precautionary statements:

Prevention:

P261 Avoid breathing dust / fume / gas / mist / vapours / spray.

P202 Do not handle until all safety precautions have been read and understood.

P201 Obtain special instructions before use.

P280 Wear protective gloves/ protective clothing / eye protection / face protection.

Wash the hands thoroughly after handling. P264

P272 Contaminated work clothing should not be allowed out of the workplace.

Response:

P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to

do. Continue rinsing.

P308+P313 IF exposed or concerned: Get medical advice / attention. P333+P313 If skin irritation or rash occurs: Get medical advice / attention. If eye irritation persists: Get medical advice / attention. P337+P313

P302+P352 IF ON SKIN: wash with plenty of water / . .

P362+P364 Take off contaminated clothing and wash it before reuse.

P363 Wash contaminated clothing before reuse.

Storage:

Store locked up. P405

Disposal:

P501 Dispose of contents / container according to applicable law.

2.2. Other hazards

Environmental classification as for Reg. (EC) 1272/2008 (CLP):

The product is classified as hazardous for environment pursuant to the provisions set forth in EC Regulation 1272/2008 (CLP).

Classification and Hazard Statement

Hazardous to the aquatic environment, chronic toxicity, category 2

Toxic to aquatic life with long lasting effects.

Hazard pictograms:



Hazard statements:

Toxic to aquatic life with long lasting effects. H411

Precautionary statements:

Prevention:

P273 Avoid release to the environment

Response:

P391 Collect spillage. Storage:

Disposal:

P501 Dispose of contents / container according to applicable law.

Information not available

3. Composition/information on ingredients

3.2. Mixtures

Contains:

Identification Classification: x = Conc. %

BIS-[4-(2,3-EPOXIPROPOXI)PHENYL]PROPANE

CAS 1675-54-3 $77 \le x < 79$ Eye irritation, category 2 H319, Skin irritation, category 2 H315, Skin sensitization, category 1B H317, Hazardous to the aquatic environment, chronic toxicity, category 2 H411



Revision nr.2 Dated 8/23/2024 Printed on 8/23/2024 Page n. 3 / 13 Replaced revision:1 (Dated 10/10/2017)

3. Composition/information on ingredients .../>>

OXIRANE, MONO[(C12-14-ALKYLOXY)METHYL] DERIVS.

CAS 68609-97-2 15 ≤ x < 16 2,3-EPOXYPROPYL O-TOLYL ETHER

CAS 2210-79-9 5≤x<6

Skin irritation, category 2 H315, Skin sensitization, category 1 H317

Germ cell mutagenicity, category 2 H341, Skin irritation, category 2 H315, Skin sensitization, category 1 H317, Hazardous to the aquatic environment,

chronic toxicity, category 2 H411

2,6-TERT BUTYL-P-CRESOL

CAS 128-37-0 0 < x < 0.25

Hazardous to the aquatic environment, acute toxicity, category 1 H400 M=1, Hazardous to the aquatic environment, chronic toxicity, category 1 H410

M=1

The full wording of hazard (H) phrases is given in section 16 of the sheet.

4. First-aid measures

4.1. Description of first aid measures

In case of doubt or in the presence of symptoms contact a doctor and show him this document.

In case of more severe symptoms, ask for immediate medical aid.

EYES: Remove, if present, contact lenses if the situation allows you to do so easily. Wash immediately with plenty of water for at least 15 minutes, opening the eyelids fully. Get medical advice/attention.

SKIN: Take off immediately all contaminated clothing. Wash immediately and thoroughly with running water (and soap if possible). Get medical advice/attention. Avoid further contact with contaminated clothing.

INGESTION: Do not induce vomiting unless explicitly authorised by a doctor. Do not give anything by mouth to an unconscious person. Get medical advice/attention.

INHALATION: Remove victim to fresh air, away from the accident scene. In the event of respiratory symptoms (coughing, wheezing, breathing difficulty, asthma) keep the victim in a comfortable position for breathing. If necessary administer oxygen. If the subject stops breathing, administer artificial respiration. Get medical advice/attention.

Rescuer protection

It is good practice for rescuers lending support to a person who has been exposed to a chemical substance or to a mixture to wear personal protective equipment. The nature of such protection depends on the hazard level of the substance or mixture, on the type of exposure and on the extent of the contamination. In the absence of other more specific indications, use of disposable gloves in the event of possible contact with body fluids is recommended. For the type of PPE suitable for the characteristics of the substance or mixture, see section 8.

4.2. Most important symptoms and effects, both acute and delayed

Specific information on symptoms and effects caused by the product are unknown.

DELAYED EFFECTS: Based on the information currently available, there are no known cases of delayed effects following exposure to this product.

4.3. Indication of any immediate medical attention and special treatment needed

If symptoms occur, whether acute or delayed, consult a doctor.

Means to have available in the workplace for specific and immediate treatment

Running water for skin and eye wash.

5. Fire-fighting measures

5.1. Extinguishing media

SUITABLE EXTINGUISHING EQUIPMENT

The extinguishing equipment should be of the conventional kind: carbon dioxide, foam, powder and water spray.

UNSUITABLE EXTINGUISHING EQUIPMENT

None in particular.

5.2. Special hazards arising from the substance or mixture

HAZARDS CAUSED BY EXPOSURE IN THE EVENT OF FIRE

Do not breathe combustion products.

Combustion products: mainly COx

^{*} There is a batch to batch variation.



Revision nr.2 Dated 8/23/2024 Printed on 8/23/2024 Page n. 4 / 13 Replaced revision:1 (Dated 10/10/2017)

5. Fire-fighting measures

.../>>

5.3. Advice for firefighters

GENERAL INFORMATION

Use jets of water to cool the containers to prevent product decomposition and the development of substances potentially hazardous for health. Always wear full fire prevention gear. Collect extinguishing water to prevent it from draining into the sewer system. Dispose of contaminated water used for extinction and the remains of the fire according to applicable regulations.

SPECIAL PROTECTIVE EQUIPMENT FOR FIRE-FIGHTERS

Normal fire fighting clothing i.e. fire kit (BS EN 469), gloves (BS EN 659) and boots (HO specification A29 and A30) in combination with self-contained open circuit positive pressure compressed air breathing apparatus (BS EN 137).

6. Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Block the leakage if there is no hazard.

Wear suitable protective equipment (including personal protective equipment referred to under Section 8 of the safety data sheet) to prevent any contamination of skin, eyes and personal clothing. These indications apply for both processing staff and those involved in emergency procedures.

6.2. Environmental precautions

The product must not penetrate into the sewer system or come into contact with surface water or ground water.

6.3. Methods and material for containment and cleaning up

Collect the leaked product into a suitable container. Evaluate the compatibility of the container to be used, by checking section 10. Absorb the remainder with inert absorbent material.

Make sure the leakage site is well aired. Contaminated material should be disposed of in compliance with the provisions set forth in point 13.

6.4. Reference to other sections

Any information on personal protection and disposal is given in sections 8 and 13.

7. Handling and storage

7.1. Precautions for safe handling

Before handling the product, consult all the other sections of this material safety data sheet. Avoid leakage of the product into the environment. Do not eat, drink or smoke during use. Remove any contaminated clothes and personal protective equipment before entering places in which people eat.

7.2. Conditions for safe storage, including any incompatibilities

Store only in the original container. Store the containers sealed, in a well ventilated place, away from direct sunlight. Keep containers away from any incompatible materials, see section 10 for details.

7.3. Specific end use(s)

Information not available

8. Exposure controls/personal protection

8.1. Control parameters

Regulatory references:

JSA NIOSH-REL NIOSH publication No. 2005-149, 3th printing, 2007.

USA CAL/OSHA-PEL California Division of Occupational Safety and Health (Cal-OSHA) Permissible Exposure Limits

(PELs).



Revision nr.2 Dated 8/23/2024 Printed on 8/23/2024 Page n. 5 / 13 Replaced revision:1 (Dated 10/10/2017)

8. Exposure controls/personal protection

2,6-TERT BUTYL-P-CRESOL							
Threshold Limit Value							
Type	Country	TWA/8h		STEL/15mii	ı	Remarks / Observations	
		mg/m3	ppm	mg/m3	ppm		
CAL/OSHA	USA	10					
NIOSH	USA	10					

Legend:

(C) = CEILING; INHAL = Inhalable Fraction; RESP = Respirable Fraction; THORA = Thoracic Fraction.

.../>>

8.2. Exposure controls

As the use of adequate technical equipment must always take priority over personal protective equipment, make sure that the workplace is well aired through effective local aspiration. Personal protective equipment must comply with current regulations.

HAND PROTECTION

Protect hands with category III work gloves.

The following should be considered when choosing work glove material (OSHA 29 CFR 1910.138): compatibility, degradation, permeability time.

The work gloves' resistance to chemical agents should be checked before use, as it can be unpredictable. The gloves' wear time depends on the duration and type of use.

SKIN PROTECTION

Wear category I professional long-sleeved overalls and safety footwear. Wash body with soap and water after removing protective clothing. EYE PROTECTION

Wear airtight protective goggles (OSHA 29 CFR 1910.133).

RESPIRATORY PROTECTION

If the threshold value (e.g. TLV-TWA) is exceeded for the substance or one of the substances present in the product, wear a mask with a NIOSH certified filter, whose class must be chosen according to the limit of use concentration (NIOSH 42 CFR 84, OSHA 29 CFR 1910.134). In the presence of gases or vapours of various kinds and/or gases or vapours containing particulate (aerosol sprays, fumes, mists, etc.) combined filters are required.

Respiratory protection devices must be used if the technical measures adopted are not suitable for restricting the worker's exposure to the threshold values considered. The protection provided by masks is in any case limited.

If the substance considered is odourless or its olfactory threshold is higher than the corresponding TLV-TWA and in the case of an emergency, wear open-circuit compressed air breathing apparatus or external air-intake breathing apparatus. For a correct choice of respiratory protection device, see standard NIOSH 42 CFR 84, OSHA 29 CFR 1910.134.

ENVIRONMENTAL EXPOSURE CONTROLS

The emissions generated by manufacturing processes, including those generated by ventilation equipment, should be checked to ensure compliance with environmental standards.

Product residues must not be indiscriminately disposed of with waste water or by dumping in waterways.

HAND PROTECTION: Protect hands with work gloves for protection against chemical agents in nitrile or fluoroelastomer (EN 374-1:2016) at least type B or higher based on the risk assessment carried out by the company. Breakthrough time > 480 minutes.

Material thickness:

NITRILE

short contact > 0.38 mm prolonged contact > 0.55 mm

FLUOROELASTOMER

short contact > 0.50 mm

prolonged contact > 1.50 mm

FACE PROTECTION: Chemical and splash protection visor EN 166 1B 3 in transparent propionate or equivalent protection

9. Physical and chemical properties

9.1. Information on basic physical and chemical properties

Value liquid transparent typical not available	Information
not available	Reason for missing data:substance/mixture is non-polar/aprotic (eg: an organic solvent mixture)
not available not available not available > 93 °C not available	(199,4 °F)
	liquid transparent typical not available not available not available not available not available software of available of available software of available



Revision nr.2 Dated 8/23/2024 Printed on 8/23/2024 Page n. 6 / 13 Replaced revision:1 (Dated 10/10/2017)

9. Physical and chemical properties .../>>

Flammability not available
Lower explosive limit not available
Upper explosive limit not available
Vapour pressure not available
Vapour density not available
Relative density 1.1 g/cm3

Solubility soluble in organic solvents

Partition coefficient: n-octanol/water not available
Auto-ignition temperature not available
Decomposition temperature not available
Viscosity not available
Explosive properties not available
Oxidising properties not available

9.2. Other information

Total solids (250°C / 482°F) 100,00 %

10. Stability and reactivity

10.1. Reactivity

There are no particular risks of reaction with other substances in normal conditions of use.

10.2. Chemical stability

The product is stable in normal conditions of use and storage.

10.3. Possibility of hazardous reactions

No hazardous reactions are foreseeable in normal conditions of use and storage.

10.4. Conditions to avoid

None in particular. However the usual precautions used for chemical products should be respected.

10.5. Incompatible materials

BIS-[4-(2,3-EPOXIPROPOXI)PHENYL]PROPANE

Avoid contact with: acids,bases,oxidising substances.

Avoid unintended contact with amines.

10.6. Hazardous decomposition products

BIS-[4-(2,3-EPOXIPROPOXI)PHENYL]PROPANE

The decomposition products depend on the temperature, the available air and the presence of other substances.

An uncontrolled exothermic reaction of epoxy resins liberates phenolic derivatives, carbon monoxide and water.

11. Toxicological information

In the absence of experimental data for the product itself, health hazards are evaluated according to the properties of the substances it contains, using the criteria specified in the applicable regulation for classification.

It is therefore necessary to take into account the concentration of the individual hazardous substances indicated in section 3, to evaluate the toxicological effects of exposure to the product.

11.1. Information on toxicological effects

Metabolism, toxicokinetics, mechanism of action and other information

Information not available

Information on likely routes of exposure

Information not available

Delayed and immediate effects as well as chronic effects from short and long-term exposure

Information not available

Interactive effects



Revision nr.2 Dated 8/23/2024 Printed on 8/23/2024 Page n. 7 / 13 Replaced revision:1 (Dated 10/10/2017)

11. Toxicological information .../>>

Information not available

ACUTE TOXICITY

2,3-EPOXYPROPYL O-TOLYL ETHER

LD50 (Oral): 2800 mg/kg Ratto LD50 (Dermal): > 2000 mg/kg Ratto

OXIRANE, MONO[(C12-14-ALKYLOXY)METHYL] DERIVS.

LD50 (Oral): 26800 mg/kg ratto
LD50 (Dermal): > 200 mg/kg ratto

2,6-TERT BUTYL-P-CRESOL

LD50 (Oral): > 6000 mg/kg rat LD50 (Dermal): > 2000 mg/kg rat

BIS-[4-(2,3-EPOXIPROPOXI)PHENYL]PROPANE

LD50 (Oral): 15000 mg/kg Ratto
LD50 (Dermal): > 2000 mg/kg Coniglio

2,6-TERT BUTYL-P-CRESOL DL50oral: OECD Test Guideline 401 Cutaneous LD50: OECD Test Guideline 402

SKIN CORROSION / IRRITATION

Causes skin irritation

SERIOUS EYE DAMAGE / IRRITATION

Causes serious eye irritation

RESPIRATORY OR SKIN SENSITISATION

Sensitising for the skin

GERM CELL MUTAGENICITY

Suspected of causing genetic defects

CARCINOGENICITY

Does not meet the classification criteria for this hazard class

Carcinogenicity Assessment:

1675-54-3 BIS-[4-(2,3-EPOXIPROPOXI)PHENYL]PROPANE

IARC:3

128-37-0 2,6-TERT BUTYL-P-CRESOL

IARC:3

2,6-TERT BUTYL-P-CRESOL Species:Rat, male and female Application method: Oral NOAEL: 247 mg/kg bw/day Target organs: Liver

BPL: yes

REPRODUCTIVE TOXICITY

Does not meet the classification criteria for this hazard class

STOT - SINGLE EXPOSURE

Does not meet the classification criteria for this hazard class

STOT - REPEATED EXPOSURE

Does not meet the classification criteria for this hazard class



TENAX SPA EPOXART RESIN A-3TO1

Revision nr.2 Dated 8/23/2024 Printed on 8/23/2024 Page n. 8 / 13 Replaced revision:1 (Dated 10/10/2017)

11. Toxicological information ...

ASPIRATION HAZARD

Does not meet the classification criteria for this hazard class

12. Ecological information

This product is dangerous for the environment and is toxic for aquatic organisms. In the long term, it has negative effects on the aquatic environment.

12.1. Toxicity

OXIRANE, MONO[(C12-14-ALKYLOXY)METHYL] DERIVS.

LC50 - for Fish > 500 mg/l/96h Oncorhynchus mykiss

EC50 - for Crustacea 6.07 mg/l/48h Daphnia magna

EC50 - for Algae / Aquatic Plants 843.75 mg/l/72h Pseudokirchnerella subcapitata

2,6-TERT BUTYL-P-CRESOL

LC50 - for Fish 0.199 mg/l/96h

EC50 - for Crustacea 0.48 mg/l/48h Daphnia magna

EC50 - for Algae / Aquatic Plants > 0.42 mg/l/72h

EC10 for Crustacea 0.069 mg/l/48h

Chronic NOEC for Fish 0.053 mg/l

Chronic NOEC for Crustacea 0.069 mg/l

BIS-[4-(2,3-EPOXIPROPOXI)PHENYL]PROPANE

LC50 - for Fish 2 mg/l/96h Oncorhynchus mykiss

EC50 - for Crustacea 1.8 mg/l/48h Daphnia magna

EC50 - for Algae / Aquatic Plants > 11 mg/l/72h Scenedesmus capricornutum

Chronic NOEC for Fish 0.3 mg/l Daphnia Magna

Chronic NOEC for Algae / Aquatic Plants 4.2 mg/l

12.2. Persistence and degradability

BIS-[4-(2,3-EPOXIPROPOXI)PHENYL]PROPANE Significant hydrolysis: elimination 82% in 28 days.

OXIRANE, MONO[(C12-14-ALKYLOXY)METHYL] DERIVS.

Rapidly degradable

2,6-TERT BUTYL-P-CRESOL NOT rapidly degradable

BIS-[4-(2,3-EPOXIPROPOXI)PHENYL]PROPANE

NOT rapidly degradable

12.3. Bioaccumulative potential

OXIRANE, MONO[(C12-14-ALKYLOXY)METHYL] DERIVS.

Partition coefficient: n-octanol/water 3.77



TENAX SPA EPOXART RESIN A-3TO1

Revision nr.2 Dated 8/23/2024 Printed on 8/23/2024 Page n. 9 / 13 Replaced revision:1 (Dated 10/10/2017)

12. Ecological information

2,6-TERT BUTYL-P-CRESOL

BCF > 230

BIS-[4-(2,3-EPOXIPROPOXI)PHENYL]PROPANE

Partition coefficient: n-octanol/water 3.242 Log Kow

12.4. Mobility in soil

Information not available

12.5. Results of PBT and vPvB assessment

On the basis of available data, the product does not contain any PBT or vPvB in percentage ≥ than 0,1%.

12.6. Other adverse effects

Information not available

13. Disposal considerations

13.1. Waste treatment methods

Reuse, when possible. Neat product residues should be considered special non-hazardous waste.

Disposal must be performed through an authorised waste management firm, in compliance with national and local regulations.

CONTAMINATED PACKAGING

Contaminated packaging must be recovered or disposed of in compliance with national waste management regulations.

14. Transport information

14.1. UN number

ADR / RID, IMDG, IATA: UN 3082

ADR / RID: In accordance with Special Provision 375, this product, when is packed in receptacles of a capacity ≤ 5Kg or 5L, is not

submitted to ADR provisions.

IMDG: In accordance with Section 2.10.2.7 of IMDG Code, this product, when is packed in receptacles of a capacity ≤ 5Kg or

5L, is not submitted to IMDG Code provisions.

IATA: In accordance with SP A197, this product, when is packed in receptacles of a capacity ≤ 5Kg or 5L, is not submitted to

IATA dangerous goods regulations.

14.2. UN proper shipping name

ADR / RID: ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S.

(BIS-[4-(2,3-EPOXIPROPOXI)PHENYL]PROPANE; 2,3-EPOXYPROPYL O-TOLYL ETHER)

IMDG: ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S.

 $(\mathsf{BIS}\text{-}[4\text{-}(2,3\text{-}\mathsf{EPOXIPROPOXI})\mathsf{PHENYL}]\mathsf{PROPANE};\,2,3\text{-}\mathsf{EPOXYPROPYL}\;\mathsf{O}\text{-}\mathsf{TOLYL}\;\mathsf{ETHER})$

IATA: ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S.

(BIS-[4-(2,3-EPOXIPROPOXI)PHENYL]PROPANE; 2,3-EPOXYPROPYL O-TOLYL ETHER)



TENAX SPA EPOXART RESIN A-3TO1

Revision nr.2 Dated 8/23/2024 Printed on 8/23/2024 Page n. 10 / 13 Replaced revision:1 (Dated 10/10/2017)

14. Transport information .../>>

14.3. Transport hazard class(es)

ADR / RID: Class: 9

Class: 9

Label: 9

Label: 9

IATA: Class: 9 Label: 9

14.4. Packing group

IMDG:

ADR / RID, IMDG, IATA: III

14.5. Environmental hazards

ADR / RID: Environmentally Hazardous

IMDG: Marine Pollutant

IATA: Environmentally Hazardous



14.6. Special precautions for user

ADR / RID: HIN - Kemler: 90 Limited Quantities: 5 lt Tunnel restriction code: (-)

Special provision: 274, 335, 375, 601

 IMDG:
 EMS: F-A, S-F
 Limited Quantities: 5 It

 IATA:
 Cargo:
 Maximum quantity: 450 L
 Packaging instructions: 964

 Passengers:
 Maximum quantity: 450 L
 Packaging instructions: 964

Passengers: Maximum quantity: 450 L Special provision: A97, A158, A197, A215

14.7. Transport in bulk according to Annex II of Marpol and the IBC Code

Information not relevant

15. Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

U.S. Federal Regulations

TSCA:

All components of this product are listed on US Toxic Substances Control Act (TSCA) Inventory or are exempt from the listing / notification requirements.

Clean Air Act Section 112(b):

No component(s) listed.

Clean Air Act Section 602 Class I Substances:

No component(s) listed.

Clean Air Act Section 602 Class II Substances:

No component(s) listed.

Clean Water Act – Priority Pollutants:



TENAX SPA EPOXART RESIN A-3TO1

Revision nr.2 Dated 8/23/2024 Printed on 8/23/2024 Page n. 11 / 13 Replaced revision:1 (Dated 10/10/2017)

15. Regulatory information .../>>

Clean Water Act – Toxic Pollutants:

No component(s) listed.

No component(s) listed.

DEA List I Chemicals (Precursor Chemicals):

No component(s) listed.

DEA List II Chemicals (Essential Chemicals):

No component(s) listed.

EPA List of Lists:

313 Category Code:

No component(s) listed.

EPCRA 302 EHS TPQ:

No component(s) listed.

EPCRA 304 EHS RQ:

No component(s) listed.

CERCLA RQ:

No component(s) listed.

EPCRA 313 TRI:

No component(s) listed.

RCRA Code:

No component(s) listed.

CAA 112 (r) RMP TQ:

No component(s) listed.

State Regulations

Massachussetts:

128-37-0 2,6-TERT BUTYL-P-CRESOL

Minnesota:

128-37-0 2,6-TERT BUTYL-P-CRESOL

New Jersey:

128-37-0 2,6-TERT BUTYL-P-CRESOL

New York:

No component(s) listed.

Pennsylvania:

128-37-0 2,6-TERT BUTYL-P-CRESOL

California:

128-37-0 2,6-TERT BUTYL-P-CRESOL

Proposition 65:

This product does not contain any substances know to the State of California to cause cancer, reproductive harm or birth defects.

International Regulations

Substances subject to exportation reporting pursuant to Regulation (EU) 649/2012:

None

Substances subject to the Rotterdam Convention:

None

Substances subject to the Stockholm Convention:

None



Revision nr.2 Dated 8/23/2024 Printed on 8/23/2024 Page n. 12 / 13 Replaced revision:1 (Dated 10/10/2017)

16. Other information

Text of hazard (H) indications mentioned in section 2-3 of the sheet:

H341 Suspected of causing genetic defects.

H319 Causes serious eye irritation.

H315 Causes skin irritation.

H317 May cause an allergic skin reaction.

H400 Very toxic to aquatic life.

H410 Very toxic to aquatic life with long lasting effects.H411 Toxic to aquatic life with long lasting effects.

LEGEND:

- 313 CATEGORY CODE: Emergency Planning and Community Right-to Know Act Section 313 Category Code
- ADR: European Agreement concerning the carriage of Dangerous goods by Road
- ATE: Acute Toxicity Estimate
- CAA 112 ® RMP TQ: Risk Management Plan Threshold Quantity (Clean Air Act Section 112®)
- CAS: Chemical Abstract Service Number
- CE50: Effective concentration (required to induce a 50% effect)
- CERCLA RQ: Reportable Quantity (Comprehensive Environment Response, Compensation, and Liability Act)
- CLP: Regulation (EC) 1272/2008
- DEA: Drug Enforcement Administration
- EmS: Emergency Schedule
- EPA: US Environmental Protection Agency
- EPCRA: Emergency Planning and Community Right-to Know Act
- EPCRA 302 EHS TPQ: Extremely Hazardous Substance Threshold Planning Quantity (Section 302 Category Code)
- EPCRA 304 EHS RQ: Extremely Hazardous Substance Reportable Quantity (Section 304 Category Code)
- EPCRA 313 TRI: Toxics Release Inventory (Section 313 Category Code)
- GHS: Globally Harmonized System of classification and labeling of chemicals
- IATA DGR: International Air Transport Association Dangerous Goods Regulation
- IC50: Immobilization Concentration 50%
- IMDG: International Maritime Code for dangerous goods
- IMO: International Maritime Organization
- LC50: Lethal Concentration 50%
- LD50: Lethal dose 50%
- OEL: Occupational Exposure Level
- PEL: Predicted exposure level
- RCRA Code: Resource Conservation and Recovery Act Code
- REACH: Regulation (EC) 1907/2006
- REL: Recommended exposure limit
- RID: Regulation concerning the international transport of dangerous goods by train
- TLV: Threshold Limit Value
- TLV CEILING: Concentration that should not be exceeded during any time of occupational exposure.
- TSCA: Toxic Substances Control Act
- TWA: Time-weighted average exposure limit
- TWA STEL: Short-term exposure limit
- VOC: Volatile organic Compounds
- WHMIS: Workplace Hazardous Materials Information System.

GENERAL BIBLIOGRAPHY:

- GHS rev. 3
- The Merck Index. 10th Edition
- Handling Chemical Safety
- Niosh Registry of Toxic Effects of Chemical Substances
- INRS Fiche Toxicologique (toxicological sheet)
- Patty Industrial Hygiene and Toxicology
- N.I. Sax Dangerous properties of Industrial Materials-7, 1989 Edition
- ECHA website
- Database of SDS models for chemicals Ministry of Health and ISS (Istituto Superiore di Sanità) Italy
- 6 NYCRR part 597
- Cal/OSHA website
- California Safe Drinking Water and Toxic Enforcement Act
- EPA website
- Hazard Comunication Standard (HCS 2012)
- IARC website
- List Of Lists EPA: Consolidated List of Chemicals Subject to EPCRA, CERCLA and Section 112® of the Clean Air Act
- Massachussetts 105 CMR Department of public health 670.000: "Right to Know"



Revision nr.2 Dated 8/23/2024 Printed on 8/23/2024 Page n. 13 / 13 Replaced revision:1 (Dated 10/10/2017)

16. Other information .../>>

- Minensota Chapter 5206 Departemnt Of Labor and Industry Hazardous Substances, Employee "Right to Know".
- New Jersey Worker and Community Right to know Act N.J.S.A.
- NTP. 2011. Report on Carcinogens, 12th Edition.
- OSHA website
- Pennsylvania, Hazardous Substance List, Chapter 323

Note for users:

The information contained in the present sheet are based on our own knowledge on the date of the last version. Users must verify the suitability and thoroughness of provided information according to each specific use of the product.

This document must not be regarded as a guarantee on any specific product property.

The use of this product is not subject to our direct control; therefore, users must, under their own responsibility, comply with the current health and safety laws and regulations. The producer is relieved from any liability arising from improper uses. Provide appointed staff with adequate training on how to use chemical products.

CALCULATION METHODS FOR CLASSIFICATION

Product classification derives from criteria established by the OSHA Hazard Communication Standard (HCS) (29 CFR 1910.1200), unless determined otherwise in Section 11 and 12. The data for evaluation of chemical-physical properties are reported in section 9.

Changes to previous review:

The following sections were modified:

01/02/03/04/05/08/09/10/11/12/14/15/16.