

Safety Data Sheet

According to U.S.A. Federal Hazcom 2012

1. Identification

1.1. Product identifier

Code: **DOMO21A**
Product name: **DOMO 21 PARTE A**

1.2. Relevant identified uses of the substance or mixture and uses advised against

Intended use: **epoxy mastic part A**

Identified Uses	Industrial	Professional	Consumer
ADHESIVE SYSTEM/TREATMENT FOR STONE SECTOR	✓	✓	-

1.3. Details of the supplier of the safety data sheet

Name: **TENAX SPA**
Full address: **Via I Maggio, 226**
District and Country: **37020 Volargne Italy (VR)**
Tel: **+39 045 6887593**
Fax: **+39 045 6862456**

e-mail address of the competent person responsible for the Safety Data Sheet: **msds@tenax.it**

Supplier: **Tenax Usa**
7606 Whitehall Executive Center Drive Suite 400, 28273 Charlotte NC, US
Tel. 001 7045831173 - Fax 001 7045833166
info@tenaxusa.com

1.4. Emergency telephone number

For urgent inquiries refer to: **Infotrac**
US and Canada: 1-800-535-5053
Int'l: 1-352-323-3500
info@infotrac.net

2. Hazards identification

2.1. Classification of the substance or mixture

The product is classified as hazardous pursuant to the provisions set forth in OSHA Hazard Communication Standard (HCS) (29 CFR 1910.1200). The product thus requires a safety datasheet. Any additional information concerning the risks for health and/or the environment are given in sections 11 and 12 of this sheet.

Classification and Hazard Statement

Carcinogenicity, category 2	Suspected of causing cancer.
Germ cell mutagenicity, category 2	Suspected of causing genetic defects.
Reproductive toxicity, category 1B	May damage fertility or the unborn child.
Eye irritation, category 2	Causes serious eye irritation.
Skin irritation, category 2	Causes skin irritation.
Skin sensitization, category 1	May cause an allergic skin reaction.

Hazard pictograms:



Signal words: **Danger**

Hazard statements:

2. Hazards identification ... / >>

H351	Suspected of causing cancer.
H341	Suspected of causing genetic defects.
H360	May damage fertility or the unborn child.
H319	Causes serious eye irritation.
H315	Causes skin irritation.
H317	May cause an allergic skin reaction.

Precautionary statements:

Prevention:

P261	Avoid breathing dust / fume / gas / mist / vapours / spray.
P202	Do not handle until all safety precautions have been read and understood.
P201	Obtain special instructions before use.
P280	Wear protective gloves/ protective clothing / eye protection / face protection.
P264	Wash the hands thoroughly after handling.
P272	Contaminated work clothing should not be allowed out of the workplace.

Response:

P305+P351+P338	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P308+P313	IF exposed or concerned: Get medical advice / attention.
P333+P313	If skin irritation or rash occurs: Get medical advice / attention.
P337+P313	If eye irritation persists: Get medical advice / attention.
P302+P352	IF ON SKIN: wash with plenty of water / . . .
P362+P364	Take off contaminated clothing and wash it before reuse.
P363	Wash contaminated clothing before reuse.

Storage:

P405	Store locked up.
-------------	------------------

Disposal:

P501	Dispose of contents / container according to applicable law.
-------------	--

2.2. Other hazards

Environmental classification as for Reg. (EC) 1272/2008 (CLP):

The product is classified as hazardous for environment pursuant to the provisions set forth in EC Regulation 1272/2008 (CLP).

Classification and Hazard Statement

Hazardous to the aquatic environment, chronic toxicity, category 2 Toxic to aquatic life with long lasting effects.

Hazard pictograms:



Hazard statements:

H411	Toxic to aquatic life with long lasting effects.
-------------	--

Precautionary statements:

Prevention:

P273	Avoid release to the environment.
-------------	-----------------------------------

Response:

P391	Collect spillage.
-------------	-------------------

Storage:

--

Disposal:

P501	Dispose of contents / container according to applicable law.
-------------	--

Additional hazards

Information not available

3. Composition/information on ingredients

3. Composition/information on ingredients ... / >>

3.2. Mixtures

Contains:

Identification

x = Conc. %

Classification:

BIS-[4-(2,3-EPOXIPROPOXI)PHENYL]PROPANE
INDEX 603-073-00-2 50 ≤ x < 52

Eye irritation, category 2 H319, Skin irritation, category 2 H315, Skin sensitization, category 1B H317, Hazardous to the aquatic environment, chronic toxicity, category 2 H411

EC 216-823-5
CAS 1675-54-3
REACH Reg. 01-2119456619-26

2,3-EPOXYPROPYL O-TOLYL ETHER
INDEX 603-056-00-X 16 ≤ x < 17

Germ cell mutagenicity, category 2 H341, Skin irritation, category 2 H315, Skin sensitization, category 1 H317, Hazardous to the aquatic environment, chronic toxicity, category 2 H411

EC 218-645-3
CAS 2210-79-9
REACH Reg. 01-2119966907-18

TITANIUM DIOXIDE
5 ≤ x < 6

Carcinogenicity, category 2 H351

EC 236-675-5
CAS 13463-67-7
REACH Reg. 01-2119489379-17

4,4'-ISOPROPYLIDENEDIPHENOL
INDEX 604-030-00-0 2 ≤ x < 2.5

Reproductive toxicity, category 1B H360, Serious eye damage, category 1 H318, Specific target organ toxicity - single exposure, category 3 H335, Skin sensitization, category 1 H317, Hazardous to the aquatic environment, acute toxicity, category 1 H400 M=1, Hazardous to the aquatic environment, chronic toxicity, category 1 H410 M=10

EC 201-245-8
CAS 80-05-7
REACH Reg. 01-2119457856-23

PROPYLIDYNETRIMETHANOL, ETHOXYLATED, ESTERS WITH ACRYLIC ACID
0.7 ≤ x < 1

Eye irritation, category 2 H319, Skin sensitization, category 1 H317, Hazardous to the aquatic environment, chronic toxicity, category 3 H412

EC 500-066-5
CAS 28961-43-5
REACH Reg. 01-2119489900-30-XXXX

* There is a batch to batch variation.

The full wording of hazard (H) phrases is given in section 16 of the sheet.

4. First-aid measures

4.1. Description of first aid measures

EYES: Remove contact lenses, if present. Wash immediately with plenty of water for at least 15 minutes, opening the eyelids fully. If problem persists, seek medical advice.

SKIN: Remove contaminated clothing. Rinse skin with a shower immediately. Wash contaminated clothing before using it again.

INHALATION: Remove to open air. If the subject stops breathing, administer artificial respiration. Get medical advice/attention immediately.

INGESTION: Get medical advice/attention immediately. Do not induce vomiting. Do not administer anything not explicitly authorised by a doctor.

4.2. Most important symptoms and effects, both acute and delayed

Specific information on symptoms and effects caused by the product are unknown.

PROPYLIDYNETRIMETHANOL, ETHOXYLATED, ESTERS WITH ACRYLIC ACID
Itching. Rashes. Hives. May cause redness and tearing of the eyes. Burning sensation

4.3. Indication of any immediate medical attention and special treatment needed

Information not available

5. Fire-fighting measures

5.1. Extinguishing media

SUITABLE EXTINGUISHING EQUIPMENT

The extinguishing equipment should be of the conventional kind: carbon dioxide, foam, powder and water spray.

UNSUITABLE EXTINGUISHING EQUIPMENT

None in particular.

5.2. Special hazards arising from the substance or mixture

HAZARDS CAUSED BY EXPOSURE IN THE EVENT OF FIRE

Do not breathe combustion products.

Combustion products: mainly COx and calcium fumes.

5.3. Advice for firefighters

GENERAL INFORMATION

Use jets of water to cool the containers to prevent product decomposition and the development of substances potentially hazardous for health. Always wear full fire prevention gear. Collect extinguishing water to prevent it from draining into the sewer system. Dispose of contaminated water used for extinction and the remains of the fire according to applicable regulations.

SPECIAL PROTECTIVE EQUIPMENT FOR FIRE-FIGHTERS

Normal fire fighting clothing i.e. fire kit (BS EN 469), gloves (BS EN 659) and boots (HO specification A29 and A30) in combination with self-contained open circuit positive pressure compressed air breathing apparatus (BS EN 137).

6. Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Block the leakage if there is no hazard.

Wear suitable protective equipment (including personal protective equipment referred to under Section 8 of the safety data sheet) to prevent any contamination of skin, eyes and personal clothing. These indications apply for both processing staff and those involved in emergency procedures.

6.2. Environmental precautions

The product must not penetrate into the sewer system or come into contact with surface water or ground water.

6.3. Methods and material for containment and cleaning up

Collect the leaked product into a suitable container. Evaluate the compatibility of the container to be used, by checking section 10. Absorb the remainder with inert absorbent material.

Make sure the leakage site is well aired. Contaminated material should be disposed of in compliance with the provisions set forth in point 13.

6.4. Reference to other sections

Any information on personal protection and disposal is given in sections 8 and 13.

7. Handling and storage

7.1. Precautions for safe handling

Before handling the product, consult all the other sections of this material safety data sheet. Avoid leakage of the product into the environment. Do not eat, drink or smoke during use. Remove any contaminated clothes and personal protective equipment before entering places in which people eat.

7.2. Conditions for safe storage, including any incompatibilities

Store only in the original container. Store the containers sealed, in a well ventilated place, away from direct sunlight. Keep containers away from any incompatible materials, see section 10 for details.

PROPYLIDYNETRIMETHANOL, ETHOXYLATED, ESTERS WITH ACRYLIC ACID

Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F.

7. Handling and storage ... / >>

7.3. Specific end use(s)

Information not available

8. Exposure controls/personal protection

8.1. Control parameters

Regulatory References:

USA	OSHA-PEL	Occupational Exposure Limits - Limits for Air Contaminants TABLE Z-1-1910.1000.
USA	CAL/OSHA-PEL	California Division of Occupational Safety and Health (Cal-OSHA) Permissible Exposure Limits (PELs).
EU	OEL EU	Directive (EU) 2022/431; Directive (EU) 2019/1831; Directive (EU) 2019/130; Directive (EU) 2019/983; Directive (EU) 2017/2398; Directive (EU) 2017/164; Directive 2009/161/EU; Directive 2006/15/EC; Directive 2004/37/EC; Directive 2000/39/EC; Directive 98/24/EC; Directive 91/322/EEC.
	TLV-ACGIH	ACGIH 2022

TITANIUM DIOXIDE

Threshold Limit Value

Type	Country	TWA/8h mg/m3	ppm	STEL/15min mg/m3	ppm	Remarks / Observations
TLV-ACGIH	-	2.5				RESP
OSHA	USA	15				INHAL
CAL/OSHA	USA	10				INHAL
CAL/OSHA	USA	5				RESP

4,4'-ISOPROPYLIDENEDIPHENOL

Threshold Limit Value

Type	Country	TWA/8h mg/m3	ppm	STEL/15min mg/m3	ppm	Remarks / Observations
OEL	EU	2				INHAL

Legend:

(C) = CEILING ; INHAL = Inhalable Fraction ; RESP = Respirable Fraction ; THORA = Thoracic Fraction.

8.2. Exposure controls

As the use of adequate technical equipment must always take priority over personal protective equipment, make sure that the workplace is well aired through effective local aspiration. Personal protective equipment must comply with current regulations.

HAND PROTECTION

Protect hands with category III work gloves.

The following should be considered when choosing work glove material (OSHA 29 CFR 1910.138): compatibility, degradation, failure time and permeability.

The work gloves' resistance to chemical agents should be checked before use, as it can be unpredictable. The gloves' wear time depends on the duration and type of use.

SKIN PROTECTION

Wear category I professional long-sleeved overalls and safety footwear. Wash body with soap and water after removing protective clothing.

EYE PROTECTION

Wear airtight protective goggles (OSHA 29 CFR 1910.133).

RESPIRATORY PROTECTION

If the threshold value (e.g. TLV-TWA) is exceeded for the substance or one of the substances present in the product, wear a mask with a NIOSH certified filter, whose class must be chosen according to the limit of use concentration (NIOSH 42 CFR 84, OSHA 29 CFR 1910.134). In the presence of gases or vapours of various kinds and/or gases or vapours containing particulate (aerosol sprays, fumes, mists, etc.) combined filters are required.

Respiratory protection devices must be used if the technical measures adopted are not suitable for restricting the worker's exposure to the threshold values considered. The protection provided by masks is in any case limited.

If the substance considered is odourless or its olfactory threshold is higher than the corresponding TLV-TWA and in the case of an emergency, wear open-circuit compressed air breathing apparatus or external air-intake breathing apparatus. For a correct choice of respiratory protection device, see standard NIOSH 42 CFR 84, OSHA 29 CFR 1910.134.

ENVIRONMENTAL EXPOSURE CONTROLS

The emissions generated by manufacturing processes, including those generated by ventilation equipment, should be checked to ensure compliance with environmental standards.

Product residues must not be indiscriminately disposed of with waste water or by dumping in waterways.

HAND PROTECTION: Protect hands with work gloves for protection from chemical agents in nitrile or fluoroelastomer (EN 374-1: 2016) at least type B or higher based on the risk assessment carried out by the company. Breakthrough time > 480 minutes.

Material thickness:
 NITRILE
 short contact> 0.38 mm
 prolonged contact> 0.55 mm
 FLUROELASTOMER
 short contact> 0.50 mm
 prolonged contact> 1.50 mm

9. Physical and chemical properties

9.1. Information on basic physical and chemical properties

Properties	Value	Information
Appearance	paste	
Colour	various	
Odour	characteristic	
Odour threshold	not available	
pH	not available	Reason for missing data:substance/mixture is non-polar/aprotic (eg: an organic solvent mixture)
Melting point / freezing point	not available	
Initial boiling point	not available	
Boiling range	not available	
Flash point	> 93 °C	(199,4 °F)
Evaporation rate	not available	
Flammability	not available	
Lower inflammability limit	not available	
Upper inflammability limit	not available	
Lower explosive limit	not available	
Upper explosive limit	not available	
Vapour pressure	not available	
Vapour density	not available	
Relative density	1.36 g/cm ³	
Solubility	insoluble in water	
Partition coefficient: n-octanol/water	not available	
Auto-ignition temperature	not available	
Decomposition temperature	not available	
Viscosity	not available	
Explosive properties	not available	
Oxidising properties	not available	

9.2. Other information

Information not available

10. Stability and reactivity

10.1. Reactivity

There are no particular risks of reaction with other substances in normal conditions of use.

10.2. Chemical stability

The product is stable in normal conditions of use and storage.

10.3. Possibility of hazardous reactions

No hazardous reactions are foreseeable in normal conditions of use and storage.

10.4. Conditions to avoid

None in particular. However the usual precautions used for chemical products should be respected.

10.5. Incompatible materials

BIS-[4-(2,3-EPOXIPROPOXI)PHENYL]PROPANE

Avoid contact with: acids,bases,oxidising substances.

10. Stability and reactivity ... / >>

Avoid unintentional contact with amines.

10.6. Hazardous decomposition products

BIS-[4-(2,3-EPOXYPROPOXI)PHENYL]PROPANE

The decomposition products depend on the temperature, the available air and the presence of other substances.

An uncontrolled exothermic reaction of epoxy resins liberates phenolic derivatives, carbon monoxide and water.

11. Toxicological information

In the absence of experimental data for the product itself, health hazards are evaluated according to the properties of the substances it contains, using the criteria specified in the applicable regulation for classification.

It is therefore necessary to take into account the concentration of the individual hazardous substances indicated in section 3, to evaluate the toxicological effects of exposure to the product.

11.1. Information on toxicological effects

Metabolism, toxicokinetics, mechanism of action and other information

Information not available

Information on likely routes of exposure

Information not available

Delayed and immediate effects as well as chronic effects from short and long-term exposure

Information not available

Interactive effects

Information not available

ACUTE TOXICITY

2,3-EPOXYPROPYL O-TOLYL ETHER

LD50 (Oral): 2800 mg/kg Ratto
LD50 (Dermal): > 2000 mg/kg Ratto

TITANIUM DIOXIDE

LD50 (Oral): > 5000 mg/kg Ratto
LD50 (Dermal): > 10000 mg/kg Coniglio
LC50 (Inhalation mists/powders): > 6.82 mg/l/4h Ratto

4,4'-ISOPROPYLIDENEDIPHENOL

LD50 (Oral): 5000 mg/kg
LD50 (Dermal): 3000 mg/kg Rabbit

BIS-[4-(2,3-EPOXYPROPOXI)PHENYL]PROPANE

LD50 (Oral): 11400 mg/kg Ratto
LD50 (Dermal): 2000 mg/kg Ratto

PROPYLIDYNETRIMETHANOL, ETHOXYLATED, ESTERS WITH ACRYLIC ACID

LD50 (Oral): > 2000 mg/kg
LD50 (Dermal): > 13200 mg/kg

SKIN CORROSION / IRRITATION

Causes skin irritation

PROPYLIDYNETRIMETHANOL, ETHOXYLATED, ESTERS WITH ACRYLIC ACID

OECD 404
Rabbit
Route of Exposure: Dermal
Effective dose: 0.5 mL
Exposure time: 4 hours
Result: non-irritating

SERIOUS EYE DAMAGE / IRRITATION

11. Toxicological information ... / >>

Causes serious eye irritation

PROPYLIDYNETRIMETHANOL, ETHOXYLATED, ESTERS WITH ACRYLIC ACID
OECD 405
Rabbit
Route of exposure: eye
Effective dose 0.1 mL
Exposure time: 24 hours
Result: Irritating

RESPIRATORY OR SKIN SENSITISATION

Sensitising for the skin

Respiratory sensitization

PROPYLIDYNETRIMETHANOL, ETHOXYLATED, ESTERS WITH ACRYLIC ACID
OECD 406
guinea pig
Route of Exposure: Dermal
Result: Sensitizing

GERM CELL MUTAGENICITY

Suspected of causing genetic defects

PROPYLIDYNETRIMETHANOL, ETHOXYLATED, ESTERS WITH ACRYLIC ACID
OECD 474
Species: live
Result: Negative

CARCINOGENICITY

Suspected of causing cancer

Carcinogenicity Assessment:

1675-54-3 BIS-[4-(2,3-EPOXIPROPOXI)PHENYL]PROPANE
IARC:3
13463-67-7 TITANIUM DIOXIDE
ACGIH:: A4
IARC:2B
7631-86-9 AMORPHOUS SILICATE HYDRATE
IARC:3

REPRODUCTIVE TOXICITY

May damage fertility or the unborn child

PROPYLIDYNETRIMETHANOL, ETHOXYLATED, ESTERS WITH ACRYLIC ACID
OECD 422: Combined Repeat Dose Toxicity Study with Reproductive and Developmental Toxicity Screening Test
Species: Rat
Result: NOAEL (No observed adverse effect level) 750 mg/kg bw/d

OECD 414: Pre-natal developmental toxicity study
Species: Rat
Result: NOAEL (No observed adverse effect level) > 1000 mg/kg bw/d

STOT - SINGLE EXPOSURE

Does not meet the classification criteria for this hazard class

STOT - REPEATED EXPOSURE

Does not meet the classification criteria for this hazard class

PROPYLIDYNETRIMETHANOL, ETHOXYLATED, ESTERS WITH ACRYLIC ACID
OECD 422: Combined Repeat Dose Toxicity Study with Reproductive and Developmental Toxicity Screening Test
Species: Rat
Route of Exposure: Oral
Exposure time: 28 days
Result: NOAEL (No observed adverse effect level) 250 mg/kg bw/d

11. Toxicological information ... / >>

Species: Rat
Route of Exposure: Dermal
Exposure time: 16 days
Result: NOAEL (No observed adverse effect level) 25 mg/kg bw/d

ASPIRATION HAZARD

Does not meet the classification criteria for this hazard class

12. Ecological information

This product is dangerous for the environment and is toxic for aquatic organisms. In the long term, it have negative effects on acquatic environment.

12.1. Toxicity

TITANIUM DIOXIDE

LC50 - for Fish > 1000 mg/l/96h
EC50 - for Crustacea > 1000 mg/l/48h Daphnia
EC50 - for Algae / Aquatic Plants > 61 mg/l/72h Pseudokirchneriella subcapitata

4,4'-ISOPROPYLIDENEDIPHENOL

LC50 - for Fish 9.4 mg/l/96h Menidia menidia
EC50 - for Crustacea 10.2 mg/l/48h Daphnia magna

BIS-[4-(2,3-EPOXIPROPOXI)PHENYL]PROPANE

LC50 - for Fish 1.3 mg/l/96h
EC50 - for Crustacea 2.1 mg/l/48h Dafnia
EC50 - for Algae / Aquatic Plants > 11 mg/l/72h

Chronic NOEC for Crustacea 0.3 mg/l Dafnia

PROPYLIDYNETRIMETHANOL, ETHOXYLATED, ESTERS WITH ACRYLIC ACID

LC50 - for Fish 1.95 mg/l/96h Danio Rerio
EC50 - for Crustacea 70.7 mg/l/48h Daphnia Magna
EC50 - for Algae / Aquatic Plants 2.2 mg/l/72h Desmodesmus subspicatus

12.2. Persistence and degradability

PROPYLIDYNETRIMETHANOL, ETHOXYLATED, ESTERS WITH ACRYLIC ACID

OECD 301B
CO2 evolution test
28 days
Biodegradation: 58 - 61%

TITANIUM DIOXIDE

Solubility in water < 0.001 mg/l
Degradability: information not available

12. Ecological information ... / >>

4,4'-ISOPROPYLIDENEDIPHENOL

Solubility in water 301 mg/l
Rapidly degradable

BIS-[4-(2,3-EPOXIPROPOXI)PHENYL]PROPANE
NOT rapidly degradable

PROPYLIDYNETRIMETHANOL, ETHOXYLATED, ESTERS WITH ACRYLIC ACID
Rapidly degradable

12.3. Bioaccumulative potential

4,4'-ISOPROPYLIDENEDIPHENOL

Partition coefficient: n-octanol/water 3.4

PROPYLIDYNETRIMETHANOL, ETHOXYLATED, ESTERS WITH ACRYLIC ACID

Partition coefficient: n-octanol/water 2.89

12.4. Mobility in soil

4,4'-ISOPROPYLIDENEDIPHENOL

Partition coefficient: soil/water 2.95

12.5. Results of PBT and vPvB assessment

On the basis of available data, the product does not contain any PBT or vPvB in percentage \geq than 0,1%.

12.6. Other adverse effects

Information not available

13. Disposal considerations

13.1. Waste treatment methods

Reuse, when possible. Neat product residues should be considered special non-hazardous waste.
Disposal must be performed through an authorised waste management firm, in compliance with national and local regulations.
CONTAMINATED PACKAGING
Contaminated packaging must be recovered or disposed of in compliance with national waste management regulations.

14. Transport information

14.1. UN number

ADR / RID, IMDG, IATA: 3082

ADR / RID: In accordance with Special Provision 375, this product, when is packed in receptacles of a capacity \leq 5Kg or 5L, is not submitted to ADR provisions.

IMDG: In accordance with Section 2.10.2.7 of IMDG Code, this product, when is packed in receptacles of a capacity \leq 5Kg or 5L, is not submitted to IMDG Code provisions.

IATA: In accordance with SP A197, this product, when is packed in receptacles of a capacity \leq 5Kg or 5L, is not submitted to IATA dangerous goods regulations.

14.2. UN proper shipping name

ADR / RID: ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S.
(BIS-[4-(2,3-EPOXIPROPOXI)PHENYL]PROPANE; 2,3-EPOXYPROPYL O-TOLYL ETHER)

IMDG: ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S.
(BIS-[4-(2,3-EPOXIPROPOXI)PHENYL]PROPANE; 2,3-EPOXYPROPYL O-TOLYL ETHER)

IATA: ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S.
(BIS-[4-(2,3-EPOXIPROPOXI)PHENYL]PROPANE; 2,3-EPOXYPROPYL O-TOLYL ETHER)

14. Transport information ... / >>

14.3. Transport hazard class(es)

ADR / RID: Class: 9 Label: 9



IMDG: Class: 9 Label: 9



IATA: Class: 9 Label: 9



14.4. Packing group

ADR / RID, IMDG, IATA: III

14.5. Environmental hazards

ADR / RID: Environmentally Hazardous



IMDG: Marine Pollutant



IATA: Environmentally Hazardous



14.6. Special precautions for user

ADR / RID:	HIN - Kemler: 90	Limited Quantities: 5 L	Tunnel restriction code: (-)
	Special provision: -		
IMDG:	EMS: F-A, S-F	Limited Quantities: 5 L	
IATA:	Cargo:	Maximum quantity: 450 L	Packaging instructions: 964
	Passengers:	Maximum quantity: 450 L	Packaging instructions: 964
	Special provision:	A97, A158, A197, A215	

14.7. Transport in bulk according to Annex II of Marpol and the IBC Code

Information not relevant

15. Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

U.S. Federal Regulations

TSCA:

All components of this product are listed on US Toxic Substances Control Act (TSCA) Inventory or are exempt from the listing / notification requirements.

Clean Air Act Section 112(b):

No component(s) listed.

Clean Air Act Section 602 Class I Substances:

No component(s) listed.

Clean Air Act Section 602 Class II Substances:

No component(s) listed.

Clean Water Act – Priority Pollutants:

15. Regulatory information ... / >>

No component(s) listed.

Clean Water Act – Toxic Pollutants:

No component(s) listed.

DEA List I Chemicals (Precursor Chemicals):

No component(s) listed.

DEA List II Chemicals (Essential Chemicals):

No component(s) listed.

EPA List of Lists:

313 Category Code:

80-05-7 4,4'-ISOPROPYLIDENEDIPHENOL (Phenols)

EPCRA 302 EHS TPQ:

No component(s) listed.

EPCRA 304 EHS RQ:

No component(s) listed.

CERCLA RQ:

No component(s) listed.

EPCRA 313 TRI:

80-05-7 4,4'-ISOPROPYLIDENEDIPHENOL (Phenols)

RCRA Code:

No component(s) listed.

CAA 112 (r) RMP TQ:

No component(s) listed.

State Regulations

Massachusetts:

7631-86-9 AMORPHOUS SILICATE HYDRATE
13463-67-7 TITANIUM DIOXIDE
80-05-7 4,4'-ISOPROPYLIDENEDIPHENOL (Phenols)

Minnesota:

7631-86-9 AMORPHOUS SILICATE HYDRATE
13463-67-7 TITANIUM DIOXIDE

New Jersey:

13463-67-7 TITANIUM DIOXIDE
80-05-7 4,4'-ISOPROPYLIDENEDIPHENOL (Phenols)

New York:

No component(s) listed.

Pennsylvania:

7631-86-9 AMORPHOUS SILICATE HYDRATE
13463-67-7 TITANIUM DIOXIDE
80-05-7 4,4'-ISOPROPYLIDENEDIPHENOL (Phenols)

California:

7631-86-9 AMORPHOUS SILICATE HYDRATE
80-05-7 4,4'-ISOPROPYLIDENEDIPHENOL (Phenols)

Proposition 65:

WARNING! This product contains chemicals known to the State of California to cause cancer and birth defects or reproductive harm.

13463-67-7 TITANIUM DIOXIDE

Hazard type	NSRL / MADL (µg/day)				Note
	Oral	Dermal	Inhalation	Intravenous	

International Regulations

Substances subject to exportation reporting pursuant to Regulation (EU) 649/2012:

15. Regulatory information ... / >>

None

Substances subject to the Rotterdam Convention:
 None

Substances subject to the Stockholm Convention:
 None

16. Other information

Text of hazard (H) indications mentioned in section 2-3 of the sheet:

H351	Suspected of causing cancer.
H341	Suspected of causing genetic defects.
H360	May damage fertility or the unborn child.
H318	Causes serious eye damage.
H319	Causes serious eye irritation.
H315	Causes skin irritation.
H335	May cause respiratory irritation.
H317	May cause an allergic skin reaction.
H400	Very toxic to aquatic life.
H410	Very toxic to aquatic life with long lasting effects.
H411	Toxic to aquatic life with long lasting effects.
H412	Harmful to aquatic life with long lasting effects.

LEGEND:

- 313 CATEGORY CODE: Emergency Planning and Community Right-to Know Act Section 313 Category Code
- ADR: European Agreement concerning the carriage of Dangerous goods by Road
- ATE: Acute Toxicity Estimate
- CAA 112 © RMP TQ: Risk Management Plan Threshold Quantity (Clean Air Act Section 112©)
- CAS: Chemical Abstract Service Number
- CE50: Effective concentration (required to induce a 50% effect)
- CERCLA RQ: Reportable Quantity (Comprehensive Environment Response, Compensation, and Liability Act)
- CLP: Regulation (EC) 1272/2008
- DEA: Drug Enforcement Administration
- EmS: Emergency Schedule
- EPA: US Environmental Protection Agency
- EPCRA: Emergency Planning and Community Right-to Know Act
- EPCRA 302 EHS TPQ: Extremely Hazardous Substance Threshold Planning Quantity (Section 302 Category Code)
- EPCRA 304 EHS RQ: Extremely Hazardous Substance Reportable Quantity (Section 304 Category Code)
- EPCRA 313 TRI: Toxics Release Inventory (Section 313 Category Code)
- GHS: Globally Harmonized System of classification and labeling of chemicals
- IATA DGR: International Air Transport Association Dangerous Goods Regulation
- IC50: Immobilization Concentration 50%
- IMDG: International Maritime Code for dangerous goods
- IMO: International Maritime Organization
- LC50: Lethal Concentration 50%
- LD50: Lethal dose 50%
- OEL: Occupational Exposure Level
- PEL: Predicted exposure level
- RCRA Code: Resource Conservation and Recovery Act Code
- REACH: Regulation (EC) 1907/2006
- REL: Recommended exposure limit
- RID: Regulation concerning the international transport of dangerous goods by train
- TLV: Threshold Limit Value
- TLV CEILING: Concentration that should not be exceeded during any time of occupational exposure.
- TSCA: Toxic Substances Control Act
- TWA: Time-weighted average exposure limit
- TWA STEL: Short-term exposure limit
- VOC: Volatile organic Compounds
- WHMIS: Workplace Hazardous Materials Information System.

GENERAL BIBLIOGRAPHY:

- GHS rev. 3
- The Merck Index. 10th Edition
- Handling Chemical Safety
- Niosh - Registry of Toxic Effects of Chemical Substances
- INRS - Fiche Toxicologique (toxicological sheet)
- Patty - Industrial Hygiene and Toxicology
- N.I. Sax - Dangerous properties of Industrial Materials-7, 1989 Edition

16. Other information ... / >>

- ECHA website
- Database of SDS models for chemicals - Ministry of Health and ISS (Istituto Superiore di Sanità) - Italy

- 6 NYCRR part 597
- Cal/OSHA website
- California Safe Drinking Water and Toxic Enforcement Act
- EPA website
- Hazard Communication Standard (HCS 2012)
- IARC website
- List Of Lists EPA: Consolidated List of Chemicals Subject to EPCRA, CERCLA and Section 112© of the Clean Air Act
- Massachusetts 105 CMR Department of public health 670.000: "Right to Know"
- Minnesota Chapter 5206 Department Of Labor and Industry Hazardous Substances, Employee "Right to Know".
- New Jersey Worker and Community Right to know Act N.J.S.A.
- NTP. 2011. Report on Carcinogens, 12th Edition.
- OSHA website
- Pennsylvania, Hazardous Substance List, Chapter 323

Note for users:

The information contained in the present sheet are based on our own knowledge on the date of the last version. Users must verify the suitability and thoroughness of provided information according to each specific use of the product.

This document must not be regarded as a guarantee on any specific product property.

The use of this product is not subject to our direct control; therefore, users must, under their own responsibility, comply with the current health and safety laws and regulations. The producer is relieved from any liability arising from improper uses.

Provide appointed staff with adequate training on how to use chemical products.

CALCULATION METHODS FOR CLASSIFICATION

Product classification derives from criteria established by the OSHA Hazard Communication Standard (HCS) (29 CFR 1910.1200), unless determined otherwise in Section 11 and 12. The data for evaluation of chemical-physical properties are reported in section 9.

Changes to previous review:

The following sections were modified:

02 / 03 / 04 / 07 / 11 / 12 / 15 / 16.