

**Safety Data Sheet**

According to U.S.A. Federal Hazcom 2012

**1. Identification**

**1.1. Product identifier**

Code: **LIQUIDO TRASPARENTE**  
Product name: **LIQUIDO TRASPARENTE**

**1.2. Relevant identified uses of the substance or mixture and uses advised against**

Intended use: **Transparent polyester glue for stones.**

Identified Uses	Industrial	Professional	Consumer
<b>ADHESIVE SYSTEM/TREATMENT FOR STONE SECTOR</b>	✓	✓	-

**1.3. Details of the supplier of the safety data sheet**

Name: **TENAX SPA**  
Full address: **Via I Maggio, 226**  
District and Country: **37020 Volargne Italy (VR)**

Tel: **+39 045 6887593**  
Fax: **+39 045 6862456**

e-mail address of the competent person responsible for the Safety Data Sheet: **msds@tenax.it**

Supplier: **Tenax Usa**  
**7606 Whitehall Executive Center Drive Suite 400, 28273 Charlotte NC, US**  
Tel. 001 7045831173 - Fax 001 7045833166  
**info@tenaxusa.com**

**1.4. Emergency telephone number**

For urgent inquiries refer to: **Infotrac**  
**US and Canada: 1-800-535-5053**  
**Int'l: 1-352-323-3500**  
**info@infotrac.net**

**2. Hazards identification**

**2.1. Classification of the substance or mixture**

The product is classified as hazardous pursuant to the provisions set forth in OSHA Hazard Communication Standard (HCS) (29 CFR 1910.1200). The product thus requires a safety datasheet. Any additional information concerning the risks for health and/or the environment are given in sections 11 and 12 of this sheet.

Classification and Hazard Statement

Flammable liquid, category 3	Flammable liquid and vapour.
Reproductive toxicity, category 2	Suspected of damaging fertility or the unborn child.
Specific target organ toxicity - repeated exposure, category 1	Causes damage to organs through prolonged or repeated exposure.
Eye irritation, category 2	Causes serious eye irritation.
Skin irritation, category 2	Causes skin irritation.
Specific target organ toxicity - single exposure, category 3	May cause respiratory irritation.
Skin sensitization, category 1A	May cause an allergic skin reaction.

Hazard pictograms:



### 2. Hazards identification ... / >>

Signal words:                      Danger

Hazard statements:

- H226**                      Flammable liquid and vapour.
- H361**                      Suspected of damaging fertility or the unborn child.
- H372**                      Causes damage to organs through prolonged or repeated exposure.
- H319**                      Causes serious eye irritation.
- H315**                      Causes skin irritation.
- H335**                      May cause respiratory irritation.
- H317**                      May cause an allergic skin reaction.

Precautionary statements:

Prevention:

- P210**                      Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
- P260**                      Do not breathe dust / fume / gas / mist / vapours / spray.
- P202**                      Do not handle until all safety precautions have been read and understood.
- P242**                      Use only non-sparking tools.
- P201**                      Obtain special instructions before use.
- P280**                      Wear protective gloves/ protective clothing / eye protection / face protection.
- P270**                      Do not eat, drink or smoke when using this product.
- P271**                      Use only outdoors or in a well-ventilated area.
- P264**                      Wash the hands thoroughly after handling.
- P240**                      Ground / bond container and receiving equipment.
- P243**                      Take precautionary measures against static discharge.
- P241**                      Use explosion-proof electrical / ventilating / lighting / . . . / equipment.
- P272**                      Contaminated work clothing should not be allowed out of the workplace.

Response:

- P305+P351+P338**                      IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
- P303+P361+P353**                      IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water / shower.
- P308+P313**                      IF exposed or concerned: Get medical advice / attention.
- P312**                      Call a POISON CENTER / doctor / . . . / if you feel unwell.
- P333+P313**                      If skin irritation or rash occurs: Get medical advice / attention.
- P337+P313**                      If eye irritation persists: Get medical advice / attention.
- P304+P340**                      IF INHALED: remove person to fresh air and keep comfortable for breathing.
- P302+P352**                      IF ON SKIN: wash with plenty of water / . . .
- P362+P364**                      Take off contaminated clothing and wash it before reuse.
- P370+P378**                      In case of fire: use CO<sub>2</sub>, sand, powder to extinguish.
- P363**                      Wash contaminated clothing before reuse.

Storage:

- P403+P235**                      Store in a well-ventilated place. Keep cool.
- P403+P233**                      Store in a well-ventilated place. Keep container tightly closed.
- P405**                      Store locked up.

Disposal:

- P501**                      Dispose of contents / container according to applicable law.

### 2.2. Other hazards

Environmental classification as for Reg. (EC) 1272/2008 (CLP):

The product is classified as hazardous for environment pursuant to the provisions set forth in EC Regulation 1272/2008 (CLP).

Classification and Hazard Statement

Hazardous to the aquatic environment, chronic toxicity, category 3                      Harmful to aquatic life with long lasting effects.

Hazard statements:

- H412**                      Harmful to aquatic life with long lasting effects.

Precautionary statements:

Prevention:

- P273**                      Avoid release to the environment.

Response:

--

Storage:

--

Disposal:

- P501**                      Dispose of contents / container according to applicable law.

Additional hazards

Information not available

### 3. Composition/information on ingredients

#### 3.2. Mixtures

Contains:

Identification	x = Conc. %	Classification:
<b>STYRENE</b>		
INDEX 601-026-00-0	27 ≤ x < 29	<b>Flammable liquid, category 3 H226, Reproductive toxicity, category 2 H361, Acute toxicity, category 4 H332, Specific target organ toxicity - repeated exposure, category 1 H372, Aspiration hazard, category 1 H304, Eye irritation, category 2 H319, Skin irritation, category 2 H315, Specific target organ toxicity - single exposure, category 3 H335, Hazardous to the aquatic environment, chronic toxicity, category 3 H412</b>
EC 202-851-5		
CAS 100-42-5		
REACH Reg. 01-2119457861-32		
<b>MALEIC ANHYDRIDE</b>		
INDEX 607-096-00-9	0.05 ≤ x < 0.1	<b>Acute toxicity, category 4 H302, Specific target organ toxicity - repeated exposure, category 1 H372, Skin corrosion, category 1B H314, Serious eye damage, category 1 H318, Respiratory sensitization, category 1 H334, Skin sensitization, category 1A H317</b>
EC 203-571-6		
CAS 108-31-6		
REACH Reg. 01-2119472428-31		

\* There is a batch to batch variation.

The full wording of hazard (H) phrases is given in section 16 of the sheet.

### 4. First-aid measures

#### 4.1. Description of first aid measures

**EYES:** Remove contact lenses, if present. Wash immediately with plenty of water for at least 30-60 minutes, opening the eyelids fully. Get medical advice/attention.

**SKIN:** Remove contaminated clothing. Rinse skin with a shower immediately. Get medical advice/attention.

**INGESTION:** Have the subject drink as much water as possible. Get medical advice/attention. Do not induce vomiting unless explicitly authorised by a doctor.

**INHALATION:** Get medical advice/attention immediately. Remove victim to fresh air, away from the accident scene. If the subject stops breathing, administer artificial respiration. Take suitable precautions for rescue workers.

#### 4.2. Most important symptoms and effects, both acute and delayed

Specific information on symptoms and effects caused by the product are unknown.

#### 4.3. Indication of any immediate medical attention and special treatment needed

Information not available

### 5. Fire-fighting measures

#### 5.1. Extinguishing media

SUITABLE EXTINGUISHING EQUIPMENT

Extinguishing substances are: carbon dioxide, foam, chemical powder. For product loss or leakage that has not caught fire, water spray can be used to disperse flammable vapours and protect those trying to stem the leak.

UNSUITABLE EXTINGUISHING EQUIPMENT

Do not use jets of water. Water is not effective for putting out fires but can be used to cool containers exposed to flames to prevent explosions.

#### 5.2. Special hazards arising from the substance or mixture

HAZARDS CAUSED BY EXPOSURE IN THE EVENT OF FIRE

Excess pressure may form in containers exposed to fire at a risk of explosion. Do not breathe combustion products.

### 5. Fire-fighting measures ... / >>

Combustion products: mainly COx

#### 5.3. Advice for firefighters

##### GENERAL INFORMATION

Use jets of water to cool the containers to prevent product decomposition and the development of substances potentially hazardous for health. Always wear full fire prevention gear. Collect extinguishing water to prevent it from draining into the sewer system. Dispose of contaminated water used for extinction and the remains of the fire according to applicable regulations.

##### SPECIAL PROTECTIVE EQUIPMENT FOR FIRE-FIGHTERS

Normal fire fighting clothing i.e. fire kit (BS EN 469), gloves (BS EN 659) and boots (HO specification A29 and A30) in combination with self-contained open circuit positive pressure compressed air breathing apparatus (BS EN 137).

### 6. Accidental release measures

#### 6.1. Personal precautions, protective equipment and emergency procedures

Block the leakage if there is no hazard.

Wear suitable protective equipment (including personal protective equipment referred to under Section 8 of the safety data sheet) to prevent any contamination of skin, eyes and personal clothing. These indications apply for both processing staff and those involved in emergency procedures.

#### 6.2. Environmental precautions

The product must not penetrate into the sewer system or come into contact with surface water or ground water.

#### 6.3. Methods and material for containment and cleaning up

Collect the leaked product into a suitable container. Evaluate the compatibility of the container to be used, by checking section 10. Absorb the remainder with inert absorbent material.

Make sure the leakage site is well aired. Contaminated material should be disposed of in compliance with the provisions set forth in point 13.

#### 6.4. Reference to other sections

Any information on personal protection and disposal is given in sections 8 and 13.

### 7. Handling and storage

#### 7.1. Precautions for safe handling

Keep away from heat, sparks and naked flames; do not smoke or use matches or lighters. Without adequate ventilation, vapours may accumulate at ground level and, if ignited, catch fire even at a distance, with the danger of backfire. Avoid bunching of electrostatic charges. Do not eat, drink or smoke during use. Remove any contaminated clothes and personal protective equipment before entering places in which people eat. Avoid leakage of the product into the environment.

#### 7.2. Conditions for safe storage, including any incompatibilities

Store only in the original container. Store in a cool and well ventilated place, keep far away from sources of heat, naked flames and sparks and other sources of ignition. Keep containers away from any incompatible materials, see section 10 for details.

#### 7.3. Specific end use(s)

Information not available

### 8. Exposure controls/personal protection

#### 8.1. Control parameters

Regulatory References:

USA	NIOSH-REL	NIOSH publication No. 2005-149, 3th printing, 2007.
USA	OSHA-PEL	Occupational Exposure Limits - Limits for Air Contaminants TABLE Z-1-1910.1000.
USA	CAL/OSHA-PEL	California Division of Occupational Safety and Health (Cal-OSHA) Permissible Exposure Limits (PELs).
	TLV-ACGIH	ACGIH 2022

### 8. Exposure controls/personal protection ... / >>

#### STYRENE

##### Threshold Limit Value

Type	Country	TWA/8h		STEL/15min		Remarks / Observations
		mg/m <sup>3</sup>	ppm	mg/m <sup>3</sup>	ppm	
TLV-ACGIH	-	10		20		
OSHA	USA		100		200	
CAL/OSHA	USA	215	50	425	100	SKIN
NIOSH	USA	215	50	425	100	

#### MALEIC ANHYDRIDE

##### Threshold Limit Value

Type	Country	TWA/8h		STEL/15min		Remarks / Observations
		mg/m <sup>3</sup>	ppm	mg/m <sup>3</sup>	ppm	
TLV-ACGIH	-	0.01	0.0025			INHAL
OSHA	USA	1	0.25			
CAL/OSHA	USA	0.4	0.1			
NIOSH	USA	1	0.25			

**Legend:**

(C) = CEILING ; INHAL = Inhalable Fraction ; RESP = Respirable Fraction ; THORA = Thoracic Fraction.

**STYRENE**

Sampling methods: [https://amcaw.ifa.dguv.de/substance/methoden/004-styrene\\_2016.pdf](https://amcaw.ifa.dguv.de/substance/methoden/004-styrene_2016.pdf)

### 8.2. Exposure controls

As the use of adequate technical equipment must always take priority over personal protective equipment, make sure that the workplace is well aired through effective local aspiration. Personal protective equipment must comply with current regulations.

**HAND PROTECTION**

Protect hands with category III work gloves.

The following should be considered when choosing work glove material (OSHA 29 CFR 1910.138): compatibility, degradation, failure time and permeability.

The work gloves' resistance to chemical agents should be checked before use, as it can be unpredictable. The gloves' wear time depends on the duration and type of use.

**SKIN PROTECTION**

Wear category I professional long-sleeved overalls and safety footwear. Wash body with soap and water after removing protective clothing.

**EYE PROTECTION**

Wear airtight protective goggles (OSHA 29 CFR 1910.133).

**RESPIRATORY PROTECTION**

If the threshold value (e.g. TLV-TWA) is exceeded for the substance or one of the substances present in the product, wear a mask with a NIOSH certified filter, whose class must be chosen according to the limit of use concentration (NIOSH 42 CFR 84, OSHA 29 CFR 1910.134). In the presence of gases or vapours of various kinds and/or gases or vapours containing particulate (aerosol sprays, fumes, mists, etc.) combined filters are required.

Respiratory protection devices must be used if the technical measures adopted are not suitable for restricting the worker's exposure to the threshold values considered. The protection provided by masks is in any case limited.

If the substance considered is odourless or its olfactory threshold is higher than the corresponding TLV-TWA and in the case of an emergency, wear open-circuit compressed air breathing apparatus or external air-intake breathing apparatus. For a correct choice of respiratory protection device, see standard NIOSH 42 CFR 84, OSHA 29 CFR 1910.134.

**ENVIRONMENTAL EXPOSURE CONTROLS**

The emissions generated by manufacturing processes, including those generated by ventilation equipment, should be checked to ensure compliance with environmental standards.

Product residues must not be indiscriminately disposed of with waste water or by dumping in waterways.

**HAND PROTECTION:** Protect hands with work gloves for protection from chemical agents in nitrile or fluoroelastomer (EN 374-1: 2016) at least type B or higher based on the risk assessment carried out by the company. Breakthrough time > 480 minutes.

Material thickness:

**NITRILE**

short contact > 0.38 mm

prolonged contact > 0.55 mm

**FLUOROELASTOMER**

short contact > 0.50 mm

prolonged contact > 1.50 mm

### 9. Physical and chemical properties

#### 9.1. Information on basic physical and chemical properties

Properties	Value	Information
Appearance	liquid	
Colour	YELLOW-RED	
Odour	typical	
Odour threshold	not available	
pH	not available	Reason for missing data:substance/mixture is non-polar/aprotic (eg: an organic solvent mixture)
Melting point / freezing point	not available	
Initial boiling point	145 °C (293 °F)	Substance:STYRENE
Boiling range	not available	
Flash point	31 °C (87,8 °F)	Substance:STYRENE
Evaporation rate	not available	
Flammability	not available	
Lower inflammability limit	not available	
Upper inflammability limit	not available	
Lower explosive limit	not available	
Upper explosive limit	not available	
Vapour pressure	not available	
Vapour density	not available	
Relative density	1.1 g/cm <sup>3</sup>	
Solubility	insoluble in water	
Partition coefficient: n-octanol/water	not available	
Auto-ignition temperature	not available	
Decomposition temperature	not available	
Viscosity	>20,5 mm <sup>2</sup> /sec (40°C)	
Explosive properties	not available	
Oxidising properties	not available	

#### 9.2. Other information

VOC : 28,50 % - 313,50 g/litre

### 10. Stability and reactivity

#### 10.1. Reactivity

There are no particular risks of reaction with other substances in normal conditions of use.

##### STYRENE

Polymerises at temperatures above 65°C/149°F. Fire hazard. Possibility of explosion.  
 Added with an inhibitor that requires a small amount of dissolved oxygen at temperatures < 25°C/77°F.

#### 10.2. Chemical stability

The product is stable in normal conditions of use and storage.

#### 10.3. Possibility of hazardous reactions

The vapours may also form explosive mixtures with the air.

##### STYRENE

May react dangerously with: peroxides, strong acids. May polymerise on contact with: aluminium trichloride, azobisisobutyronitrile, dibenzoyl peroxide, sodium. Risk of explosion on contact with: butyllithium, chlorosulphuric acid, di-tert-butyl peroxide, oxidising substances, oxygen.

#### 10.4. Conditions to avoid

Avoid overheating. Avoid bunching of electrostatic charges. Avoid all sources of ignition.

##### STYRENE

Avoid contact with: oxidising substances, copper, strong acids.

#### 10.5. Incompatible materials

##### STYRENE

Incompatible materials: plastic materials.

### 10. Stability and reactivity ... / >>

#### 10.6. Hazardous decomposition products

In the event of thermal decomposition or fire, gases and vapours that are potentially dangerous to health may be released.

### 11. Toxicological information

In the absence of experimental data for the product itself, health hazards are evaluated according to the properties of the substances it contains, using the criteria specified in the applicable regulation for classification. It is therefore necessary to take into account the concentration of the individual hazardous substances indicated in section 3, to evaluate the toxicological effects of exposure to the product.

#### 11.1. Information on toxicological effects

##### Metabolism, toxicokinetics, mechanism of action and other information

Information not available

##### Information on likely routes of exposure

STYRENE  
 WORKERS: inhalation; contact with the skin.

##### Delayed and immediate effects as well as chronic effects from short and long-term exposure

STYRENE  
 The acute toxicity by inhalation at 1000 ppm affects the central nervous system with headache and dizziness, lack of coordination; irritation of the eye and respiratory tract mucous membranes occurs at 500 ppm. Chronic exposure causes depression of the central and peripheral nervous system with loss of memory, headache and drowsiness starting at 20 ppm; digestive disorders with nausea and loss of appetite; irritation of the respiratory tract with chronic bronchitis; dermatosis. Repeated exposure, at low doses of inhaled substance, causes irreversible changes to hearing and may cause changes in colour vision. No certain data is available on the reversibility of the visual impairment. Repeated skin exposure causes irritation. The substance degrades the skin, which can cause dryness and cracking.

##### Interactive effects

STYRENE  
 The metabolism of the substance is inhibited by ethanol. When styrene is photo-oxidised with ozone and nitrogen dioxide, as in the formation of smog, products highly irritating for the human eye may ensue.

##### ACUTE TOXICITY

STYRENE  
 LD50 (Oral): 5000 mg/kg Rat  
 LC50 (Inhalation vapours): 11.8 mg/l/4h Rat

MALEIC ANHYDRIDE  
 LD50 (Oral): 1090 mg/kg Rat  
 LD50 (Dermal): 610 mg/kg Rat

##### SKIN CORROSION / IRRITATION

Causes skin irritation

##### SERIOUS EYE DAMAGE / IRRITATION

Causes serious eye irritation

##### RESPIRATORY OR SKIN SENSITISATION

Sensitising for the skin

##### GERM CELL MUTAGENICITY

Does not meet the classification criteria for this hazard class

##### CARCINOGENICITY

Does not meet the classification criteria for this hazard class  
 Carcinogenicity Assessment:





**12. Ecological information** ... / >>

**12.5. Results of PBT and vPvB assessment**

On the basis of available data, the product does not contain any PBT or vPvB in percentage  $\geq$  than 0,1%.

**12.6. Other adverse effects**

Information not available

**13. Disposal considerations**

**13.1. Waste treatment methods**

Reuse, when possible. Neat product residues should be considered special non-hazardous waste.  
Disposal must be performed through an authorised waste management firm, in compliance with national and local regulations.  
CONTAMINATED PACKAGING  
Contaminated packaging must be recovered or disposed of in compliance with national waste management regulations.

**14. Transport information**

**14.1. UN number**

ADR / RID, IMDG, IATA: 1866

**14.2. UN proper shipping name**

ADR / RID: RESIN SOLUTION  
IMDG: RESIN SOLUTION  
IATA: RESIN SOLUTION

**14.3. Transport hazard class(es)**

ADR / RID: Class: 3 Label: 3  
IMDG: Class: 3 Label: 3  
IATA: Class: 3 Label: 3



**14.4. Packing group**

ADR / RID, IMDG, IATA: III

**14.5. Environmental hazards**

ADR / RID: NO  
IMDG: NO  
IATA: NO

**14.6. Special precautions for user**

ADR / RID:	HIN - Kemler: 30 Special provision: -	Limited Quantities: 5 L	Tunnel restriction code: (D/E)
IMDG:	EMS: F-E, <u>S-E</u>	Limited Quantities: 5 L	
IATA:	Cargo: Passengers: Special provision:	Maximum quantity: 220 L Maximum quantity: 60 L A3	Packaging instructions: 366 Packaging instructions: 355

**14.7. Transport in bulk according to Annex II of Marpol and the IBC Code**

Information not relevant

**15. Regulatory information**

**15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture**

U.S. Federal Regulations

TSCA:

All components of this product are listed on US Toxic Substances Control Act (TSCA) Inventory or are exempt from the listing / notification requirements.

Clean Air Act Section 112(b):

100-42-5 STYRENE

Clean Air Act Section 602 Class I Substances:

No component(s) listed.

Clean Air Act Section 602 Class II Substances:

No component(s) listed.

Clean Water Act – Priority Pollutants:

No component(s) listed.

Clean Water Act – Toxic Pollutants:

No component(s) listed.

DEA List I Chemicals (Precursor Chemicals):

No component(s) listed.

DEA List II Chemicals (Essential Chemicals):

No component(s) listed.

EPA List of Lists:

313 Category Code:

100-42-5 STYRENE

EPCRA 302 EHS TPQ:

No component(s) listed.

EPCRA 304 EHS RQ:

No component(s) listed.

CERCLA RQ:

100-42-5 STYRENE

EPCRA 313 TRI:

100-42-5 STYRENE

RCRA Code:

No component(s) listed.

CAA 112 (r) RMP TQ:

No component(s) listed.

State Regulations

Massachusetts:

100-42-5 STYRENE

Minnesota:

100-42-5 STYRENE

New Jersey:

100-42-5 STYRENE

New York:

### 15. Regulatory information ... / >>

100-42-5 STYRENE

Pennsylvania:

100-42-5 STYRENE

California:

100-42-5 STYRENE

Proposition 65:

**WARNING!** This product contains chemicals known to the State of California to cause cancer and birth defects or reproductive harm.

#### 100-42-5 STYRENE

Hazard type	NSRL / MADL (µg/day)				Intravenous	Note
	Oral	Dermal	Inhalation			
Carcinogenicity	27					-

International Regulations

Substances subject to exportation reporting pursuant to Regulation (EU) 649/2012:

None

Substances subject to the Rotterdam Convention:

None

Substances subject to the Stockholm Convention:

None

### 16. Other information

Text of hazard (H) indications mentioned in section 2-3 of the sheet:

<b>H226</b>	Flammable liquid and vapour.
<b>H361</b>	Suspected of damaging fertility or the unborn child.
<b>H302</b>	Harmful if swallowed.
<b>H332</b>	Harmful if inhaled.
<b>H372</b>	Causes damage to organs through prolonged or repeated exposure.
<b>H304</b>	May be fatal if swallowed and enters airways.
<b>H314</b>	Causes severe skin burns and eye damage.
<b>H319</b>	Causes serious eye irritation.
<b>H315</b>	Causes skin irritation.
<b>H335</b>	May cause respiratory irritation.
<b>H334</b>	May cause allergy or asthma symptoms or breathing difficulties if inhaled.
<b>H317</b>	May cause an allergic skin reaction.
<b>H412</b>	Harmful to aquatic life with long lasting effects.

LEGEND:

- 313 CATEGORY CODE: Emergency Planning and Community Right-to Know Act Section 313 Category Code
- ADR: European Agreement concerning the carriage of Dangerous goods by Road
- ATE: Acute Toxicity Estimate
- CAA 112 © RMP TQ: Risk Management Plan Threshold Quantity (Clean Air Act Section 112©)
- CAS: Chemical Abstract Service Number
- CE50: Effective concentration (required to induce a 50% effect)
- CERCLA RQ: Reportable Quantity (Comprehensive Environment Response, Compensation, and Liability Act)
- CLP: Regulation (EC) 1272/2008
- DEA: Drug Enforcement Administration
- EmS: Emergency Schedule
- EPA: US Environmental Protection Agency
- EPCRA: Emergency Planning and Community Right-to Know Act
- EPCRA 302 EHS TPQ: Extremely Hazardous Substance Threshold Planning Quantity (Section 302 Category Code)
- EPCRA 304 EHS RQ: Extremely Hazardous Substance Reportable Quantity (Section 304 Category Code)
- EPCRA 313 TRI: Toxics Release Inventory (Section 313 Category Code)
- GHS: Globally Harmonized System of classification and labeling of chemicals
- IATA DGR: International Air Transport Association Dangerous Goods Regulation
- IC50: Immobilization Concentration 50%
- IMDG: International Maritime Code for dangerous goods
- IMO: International Maritime Organization
- LC50: Lethal Concentration 50%
- LD50: Lethal dose 50%
- OEL: Occupational Exposure Level
- PEL: Predicted exposure level
- RCRA Code: Resource Conservation and Recovery Act Code

**16. Other information** ... / >>

- REACH: Regulation (EC) 1907/2006
- REL: Recommended exposure limit
- RID: Regulation concerning the international transport of dangerous goods by train
- TLV: Threshold Limit Value
- TLV CEILING: Concentration that should not be exceeded during any time of occupational exposure.
- TSCA: Toxic Substances Control Act
- TWA: Time-weighted average exposure limit
- TWA STEL: Short-term exposure limit
- VOC: Volatile organic Compounds
- WHMIS: Workplace Hazardous Materials Information System.

**GENERAL BIBLIOGRAPHY:**

- GHS rev. 3
- The Merck Index. 10th Edition
- Handling Chemical Safety
- Niosh - Registry of Toxic Effects of Chemical Substances
- INRS - Fiche Toxicologique (toxicological sheet)
- Patty - Industrial Hygiene and Toxicology
- N.I. Sax - Dangerous properties of Industrial Materials-7, 1989 Edition
- ECHA website
- Database of SDS models for chemicals - Ministry of Health and ISS (Istituto Superiore di Sanità) - Italy
  
- 6 NYCRR part 597
- Cal/OSHA website
- California Safe Drinking Water and Toxic Enforcement Act
- EPA website
- Hazard Communication Standard (HCS 2012)
- IARC website
- List Of Lists EPA: Consolidated List of Chemicals Subject to EPCRA, CERCLA and Section 112® of the Clean Air Act
- Massachusetts 105 CMR Department of public health 670.000: "Right to Know"
- Minnesota Chapter 5206 Department Of Labor and Industry Hazardous Substances, Employee "Right to Know".
- New Jersey Worker and Community Right to know Act N.J.S.A.
- NTP. 2011. Report on Carcinogens, 12th Edition.
- OSHA website
- Pennsylvania, Hazardous Substance List, Chapter 323

**Note for users:**

The information contained in the present sheet are based on our own knowledge on the date of the last version. Users must verify the suitability and thoroughness of provided information according to each specific use of the product.

This document must not be regarded as a guarantee on any specific product property.

The use of this product is not subject to our direct control; therefore, users must, under their own responsibility, comply with the current health and safety laws and regulations. The producer is relieved from any liability arising from improper uses.

Provide appointed staff with adequate training on how to use chemical products.

**CALCULATION METHODS FOR CLASSIFICATION**

Product classification derives from criteria established by the OSHA Hazard Communication Standard (HCS) (29 CFR 1910.1200), unless determined otherwise in Section 11 and 12. The data for evaluation of chemical-physical properties are reported in section 9.

**Changes to previous review:**

The following sections were modified:

01 / 05 / 08 / 10 / 11 / 14.